








Supplier:	KEEPOWER TECHNOLOGY CO., LIMITED
Address:	Bld4, Fengmenao Industrial Park, Longgang District, Shenzhen 518129, China
Phone:	+86 755 8995 6056
Fax:	+86 755 8930 9659
E-Mail:	info@keppower.com.cn
Website:	www.keppower.com.cn

High-end Li-ion Rechargeable Cells

Brand	Size	Nominal Voltage/Capacity	Model	Photo	Full Charged Voltage	Max. Constant Discharge Current	Quick Details
Sanyo	18650	3.6V 2150mAh	UR18650A		4.20±0.03V	4300mA	1) Min. Capacity: 2080mAh 2) Charge Voltage: 4.20V 3) Discharge End-off Voltage: 3.0V 4) Standard Charge Current: 1510mA 5) Standard Charge Time: 3 hours 6) Dimension: (D)18.30*(H)64.90mm 7) Weight: Max.43.0g
	18650	3.7V 2600mAh	UR18650FM		4.20±0.03V	5000mA	1) Min. Capacity: 2500mAh 2) Charge Voltage: 4.20V 3) Discharge End-off Voltage: 3.0V 4) Standard Charge Current: 1750mA 5) Standard Charge Time: 3 hours 6) Dimension: (D)18.30*(H)64.90mm 7) Weight: Max.48.0g
	14500	3.7V 840mAh	UR14500P		4.2 ±0.05 V	1680mA	1) Min. Capacity: 800mAh 2) Charge Voltage: 4.20V 3) Discharge End-off Voltage: 2.5V 4) Standard Charge Current: 800mA 5) Standard Charge Time: 2.5 hours 6) Dimension: (D)13.90*(H)49.20mm 7) Weight: Max.20.0g
	18500	3.7V 1700mAh	UR18500F		4.2 ±0.05 V	3240mA	1) Min. Capacity: 1620mAh 2) Charge Voltage: 4.2V 3) Discharge End-off Voltage: 3.0V 4) Standard Charge Current: 1100mA 5) Standard Charge Time: 3 hours 6) Dimension: (D)18.30*(H)49.50mm 7) Weight: Max.35.0g
Panasonic	18650	3.6V 2900mAh	NCR18650PF		4.2 ±0.03 V	10A (High Power)	1) Min. Capacity: 2750mAh 2) Charge Voltage: 4.2V 3) Discharge End-off Voltage: 2.5V 4) Standard Charge Current: 1350mA 5) Standard Charge Time: 4 hours 6) Dimension: (D)18.50*(H)65.30mm 7) Weight: Max.47.0g
	18650	3.6V 3100mAh	NCR18650A		4.2 ±0.05 V	3540mA	1) Min. Capacity: 2950mAh 2) Charge Voltage: 4.2V 3) Discharge End-off Voltage: 2.5V 4) Standard Charge Current: 590mA 5) Standard Charge Time: 5 hours 6) Dimension: (D)18.50*(H)65.20mm 7) Weight: Max.46.3g
	18650	3.6V 3200mAh	NCR18650BE		4.2 ±0.05 V	3636mA	1) Min. Capacity: 3030mAh 2) Charge Voltage: 4.2V 3) Discharge End-off Voltage: 2.5V 4) Standard Charge Current: 909mA 5) Standard Charge Time: 5 hours 6) Dimension: (D)18.50*(H)65.20mm 7) Weight: Max.48.5g
	18650	3.6V 3400mAh	NCR18650B		4.20 ± 0.03V	4780mA	1) Min. Capacity: 3250mAh 2) Charge Voltage: 4.2V 3) Discharge End-off Voltage: 2.5V 4) Standard Charge Current: 1620mA 5) Standard Charge Time: 4 hours 6) Dimension: (D)18.50*(H)65.30mm 7) Weight: Max.48.5g
Sony	18650	3.7V 1600mAh	US18650VTC3		4.20±0.05V	30A (High Power)	1) Min. Capacity: 1500mAh 2) Charge Voltage: 4.2V 3) Discharge End-off Voltage: 2.5V 4) Continuous Maximum Charge Current: 10.0A 5) Continuous Maximum Discharge Current: 30.0A 6) Dimension: (D)18.20*(H)65.00mm 7) Weight: Max.46.6g
	18650	3.6V 2100mAh	US18650VTC4		4.2 ±0.05 V	30A (High Power)	1) Min. Capacity: 2000mAh 2) Charge Voltage: 4.2V 3) Discharge End-off Voltage: 2.5V 4) Continuous Maximum Charge Current: 4.0A 5) Continuous Maximum Discharge Current: 30.0A 6) Dimension: (D)18.20*(H)65.00mm 7) Weight: Max.46.5g
	18650	3.7V 2250mAh	US18650V3		4.2 ±0.05 V	10A (High Power)	1) Min. Capacity: 2150mAh 2) Charge Voltage: 4.2V 3) Discharge End-off Voltage: 2.5V 4) Continuous Maximum Charge Current: 2150mA 5) Continuous Maximum Discharge Current: 10.0A 6) Dimension: (D)18.20*(H)64.90mm 7) Weight: Max.45.1g
	18650	3.6V 2600mAh	US18650VTC5		4.2 ±0.05 V	30A (High Power)	1) Min. Capacity: 2500mAh 2) Charge Voltage: 4.2V 3) Discharge End-off Voltage: 2.5V 4) Continuous Maximum Charge Current: 4.0A 5) Continuous Maximum Discharge Current: 30.0A 6) Dimension: (D)18.20*(H)65.00mm 7) Weight: Max.46.5g

Brand	Size	Nominal Voltage/Capacity	Model	Photo	Full Charged Voltage	Max. Constant Discharge Current	Quick Details
Sony	18650	3.6V 2900mAh	US18650NC1		4.2 ±0.05 V	10A (High Power)	1) Min. Capacity: 2750mAh 2) Charge Voltage: 4.2V 3) Discharge End-off Voltage: 2.5V 4) Continuous Maximum Charge Current: 3000mA 5) Continuous Maximum Discharge Current: 8.0A 6) Dimension: (D)18.20*(H)65.20mm 7) Weight: Max.46.8g
Samsung SDI	18650	3.6V 2000mAh	INR18650-20R		4.20 ±0.05 V	22A (High Power)	1) Min. Capacity: 2000mAh 2) Charge Voltage: 4.2V 3) Discharge End-off Voltage: 2.5V 4) Standard Charge: CCCV, 1A, 4.20 ± 0.05 V, 100mA cut-off 5) Standard Charging Time: 180min / 100mA cut-off 6) Continuous Maximum Discharge Current: 22.0A 7) Dimension: (D)18.33*(H)64.85mm 8) Weight: Max.45.0g
	18650	3.6V 2200mAh	ICR18650-22F		4.20 ±0.05 V	4400mA	1) Min. Capacity: 2200mAh 2) Charge Voltage: 4.2V 3) Discharge End-off Voltage: 2.75V 4) Standard Charge Current: 1100mA 5) Standard Charging Time: 3 hours 6) Max. Discharge Current: 4400mA 7) Dimension: (D)18.40*(H)65.0mm 8) Weight: Max.44.5g
	18650	3.6V 2200mAh	ICR18650-22P		4.2V±0.05 V	10A (High Power)	1) Min. Capacity: 2050mAh 2) Charge Voltage: 4.2V 3) Discharge End-off Voltage: 2.75V 4) Standard Charge Current: 1075mA 5) Standard Charging Time: 3 hours 6) Continuous Maximum Discharge Current: 10.0A 7) Dimension: (D)18.40*(H)65.00mm 8) Weight: Max.44.5g
	18650	3.6V 2500mAh	INR18650-25R		4.2V±0.05 V	20A (High Power)	1) Min. Capacity: 2500mAh 2) Charge Voltage: 4.2V 3) Discharge End-off Voltage: 2.5V 4) Standard Charge Current: 1250mA 5) Standard Charging Time: 3 hours 6) Continuous Maximum Discharge Current: 20.0A 7) Dimension: (D)18.33*(H)64.85mm 8) Weight: Max.45.0g
	18650	3.7V 2600mAh	ICR18650-26F		4.2 ±0.05 V	5200mA	1) Min. Capacity: 2550mAh 2) Charge Voltage: 4.2V 3) Discharge End-off Voltage: 2.75V 4) Standard Charge Current: 1300mA 5) Standard Charging Time: 3 hours 6) Continuous Maximum Discharge Current: 5200mA 7) Dimension: (D)18.40*(H)65.00mm 8) Weight: Max.47.0g
	18650	3.7V 2800mAh	ICR18650-28A		4.3 ±0.03 V	5600mA	1) Min. Capacity: 2700mAh 2) Charge Voltage: 4.3V 3) Discharge End-off Voltage: 2.75V 4) Standard Charge Current: 1400mA 5) Standard Charging Time: 3 hours 6) Continuous Maximum Discharge Current: 5600mA 7) Dimension: (D)18.40*(H)65.00mm 8) Weight: Max.48.0g
	18650	3.78V 2950mAh	ICR18650-30B		4.35 ±0.03 V	5900mA	1) Min. Capacity: 2850mAh 2) Charge Voltage: 4.35V 3) Discharge End-off Voltage: 2.75V 4) Standard Charge Current: 1475mA 5) Standard Charging Time: 3 hours 6) Continuous Maximum Discharge Current: 5900mA 7) Dimension: (D)18.40*(H)65.00mm 8) Weight: Max.48.0g
	18650	3.75V 3200mAh	ICR18650-32A		4.35 ±0.05 V	6400mA	1) Min. Capacity: 3100mAh 2) Charge Voltage: 4.35V 3) Discharge End-off Voltage: 2.75V 4) Standard Charge Current: 1600mA 5) Standard Charging Time: 3 hours 6) Continuous Maximum Discharge Current: 6400mA 7) Dimension: (D)18.40*(H)65.00mm 8) Weight: Max.50.0g
LG Chem	18650	3.6V 2200mAh	ICR18650S3		4.2V	3225mA	1) Min. Capacity: 2150mAh 2) Charge Voltage: 4.2V 3) Discharge End-off Voltage: 3.0V 4) Standard Charge Current: 1075mA 5) Max. Charge Current: 2150mA 6) Continuous Maximum Discharge Current: 3225mA 7) Dimension: (D)18.24*(H)65.05mm 8) Weight: Max.47.0g
	18650	3.6V 2500mAh	ICR18650HE2		4.2V	20A (High Power)	1) Min. Capacity: 2500mAh 2) Charge Voltage: 4.2V 3) Discharge End-off Voltage: 2.5V 4) Standard Charge Current: 1250mA 5) Max. Charge Current: 4000mA 6) Continuous Maximum Discharge Current: 20A 7) Dimension: (D)18.30*(H)65.00mm 8) Weight: Max.48.0g
	18650	3.6V 2600mAh	ICR18650B4		4.2V	5000mA	1) Min. Capacity: 2500mAh 2) Charge Voltage: 4.2V 3) Discharge End-off Voltage: 2.75V 4) Standard Charge Current: 1250mA 5) Max. Charge Current: 2500mA 6) Max. Discharge Current: 5000mA 7) Dimension: (D)18.40*(H)65.05mm 8) Weight: Max.48.0g

Brand	Size	Nominal Voltage/Capacity	Model	Photo	Full Charged Voltage	Max. Constant Discharge Current	Quick Details
LG Chem	18650	3.7V 3000mAh	ICR18650D1		4.35V	5800mA	1) Min. Capacity: 2900mAh 2) Charge Voltage: 4.35V 3) Discharge End-off Voltage: 3.0V 4) Standard Charge Current: 1450mA 5) Max. Charge Current: 2900mA 6) Max. Discharge Current: 5800mA 7) Dimension: (D)18.40*(H)65.05mm 8) Weight: Max.48.5g
	18650	3.75V 3200mAh	ICR18650E1		4.35V	4650mA	1) Min. Capacity: 3100mAh 2) Charge Voltage: 4.35V 3) Discharge End-off Voltage: 2.75V 4) Standard Charge Current: 1550mA 5) Max. Charge Current: 2170mA 6) Max. Discharge Current: 4650mA 7) Dimension: (D)18.30*(H)65.05mm 8) Weight: Max.49.0g

* Please contact info@keppower.com.cn for more information.