

 Specialist in Portable Power Solution				Supplier:	KEEPPower TECHNOLOGY CO., LIMITED	
				Address:	Bld4, Fengmenao Industrial Park, Longgang District, Shenzhen 518129, China	
				Phone:	+86 755 8995 6056	
				Fax:	+86 755 8930 9659	
				E-Mail:	info@keepower.com.cn	
				Website:	www.keepower.com.cn	
Keppower High Power Battery for E-Cigarette						
Type	Model	Type	Nominal Voltage/Capacity	Photo	Max. Constant Discharge Current	Specifications
Bare Cell	Samsung INR18650-20R	Li-Mn	3.7V 2000mAh		22A	1) Min. Capacity: 2000mAh 2) Charge Voltage: 4.2V 3) Discharge End-off Voltage: 2.5V 4) Standard Charge: CCCV, 1A, 4.20 ± 0.05 V, 100mA cut-off 5) Standard Charging Time: 180min / 100mA cut-off 6) Continuous Maximum Discharge Current: 22.0A 7) Dimension: (D)18.33*(H)64.85mm 8) Weight: Max.45.0g
	Sony US18650VTC4	Li-Mn	3.7V 2100mAh		30A	1) Min. Capacity: 2000mAh 2) Charge Voltage: 4.2V 3) Discharge End-off Voltage: 2.5V 4) Continuous Maximum Charge Current: 4.0A 5) Continuous Maximum Discharge Current: 30.0A 6) Dimension: (D)18.20*(H)65.00mm 7) Weight: Max.46.5g
	Sony US18650V3	Li-Mn	3.7V 2250mAh		10A	1) Min. Capacity: 2150mAh 2) Charge Voltage: 4.2V 3) Discharge End-off Voltage: 2.5V 4) Continuous Maximum Charge Current: 2150mA 5) Continuous Maximum Discharge Current: 10.0A 6) Dimension: (D)18.20*(H)64.90mm 7) Weight: Max.45.1g
	LG ICR18650HE2	Li-Mn	3.7V 2500mAh		20A	1) Min. Capacity: 2500mAh 2) Charge Voltage: 4.2V 3) Discharge End-off Voltage: 2.5V 4) Standard Charge Current: 1250mA 5) Max. Charge Current: 4000mA 6) Continuous Maximum Discharge Current: 20A 7) Dimension: (D)18.30*(H)65.00mm 8) Weight: Max.48.0g
	Samsung INR18650-25R	Li-Mn	3.7V 2500mAh		20A	1) Min. Capacity: 2500mAh 2) Charge Voltage: 4.2V 3) Discharge End-off Voltage: 2.5V 4) Standard Charge Current: 1250mA 5) Standard Charging Time: 3 hours 6) Continuous Maximum Discharge Current: 20.0A 7) Dimension: (D)18.33*(H)64.85mm 8) Weight: Max.45.0g
	Sony US18650VTC5	Li-Mn	3.7V 2600mAh		30A	1) Min. Capacity: 2500mAh 2) Charge Voltage: 4.2V 3) Discharge End-off Voltage: 2.5V 4) Continuous Maximum Charge Current: 4.0A 5) Continuous Maximum Discharge Current: 30.0A 6) Dimension: (D)18.20*(H)65.00mm 7) Weight: Max.46.5g
	Sony US18650NC1	Li-Mn	3.7V 2900mAh		10A	1) Min. Capacity: 2800mAh 2) Charge Voltage: 4.2V 3) Discharge End-off Voltage: 2.5V 4) Continuous Maximum Charge Current: 3.0A 5) Continuous Maximum Discharge Current: 10.0A 6) Dimension: (D)18.20*(H)65.00mm 7) Weight: Max.46.0g
	Panasonic NCR18650PF	Li-ion	3.7V 2900mAh		10A	1) Min. Capacity: 2750mAh 2) Charge Voltage: 4.2V 3) Discharge End-off Voltage: 2.5V 4) Standard Charge Current: 1350mA 5) Standard Charge Time: 4 hours 6) Continuous Maximum Discharge Current: 10.0A 7) Dimension: (D)18.50*(H)65.30mm 8) Weight: Max.47.0g
	MNKE 26650-J	Li-Mn	3.7V 3800mAh		20A	1) Min. Capacity: 3700mAh 2) Charge Voltage: 4.20V±0.05 3) Discharge End-off Voltage: 2.5V 4) Maximum Charge Current: 6.5A 5) Maximum Continuous Discharge Current: 20.0A 6) Ultra Discharge Current: 60A 7) Dimension: (D)26.00*(H)65.00mm 8) Weight: Max.93.0g
Flat Top	KP-IMR18650-2000	Li-Mn	3.7V 2000mAh		22A	1) Min. Capacity: 1900mAh 2) Charge Voltage: 4.20V±0.05 3) Standard Charge Current: 1000mA 4) Standard Charge Time: 3 hours 5) Standard Discharge Cut-off Voltage: 2.75V 6) Standard Discharge Current: 400mA 7) Standard Discharge Cut-off Current: 30mA 8) Max. Constant Discharge Current: 22A 9) Dimension: (D)18.40*(H)65.60mm 10) Cycle Life: Over 500 charge & discharge cycles 11) Weight: Max. 46.0g
	KP-IMR18650-2100	Li-Mn	3.7V 2100mAh		30A	1) Min. Capacity: 2000mAh 2) Charge Voltage: 4.20V±0.05 3) Standard Charge Current: 1000mA 4) Standard Charge Time: 3 hours 5) Standard Discharge Cut-off Voltage: 2.75V 6) Standard Discharge Current: 420mA 7) Standard Discharge Cut-off Current: 30mA 8) Max. Constant Discharge Current: 30A 9) Dimension: (D)18.40*(H)65.00mm 10) Cycle Life: Over 500 charge & discharge cycles 11) Weight: Max. 48.0g

Type	Model	Type	Nominal Voltage/Capacity	Photo	Max. Constant Discharge Current	Specifications
Flat Top	KP-IMR18650-2250	Li-ion	3.7V 2250mAh		10A	1) Min. Capacity: 2150mAh 2) Charge Voltage: 4.20V±0.05 3) Standard Charge Current: 1100mA 4) Standard Charge Time: 3 hours 5) Standard Discharge Cut-off Voltage: 2.75V 6) Standard Discharge Current: 550mA 7) Standard Discharge Cut-off Current: 30mA 8) Max. Constant Discharge Current: 10A 9) Dimension: (D)18.40*(H)65.00mm 10) Cycle Life: Over 500 charge & discharge cycles 11) Weight: Max. 45.0g
	KP-IMR18650-2500	Li-Mn	3.7V 2500mAh		20A	1) Min. Capacity: 2400mAh 2) Charge Voltage: 4.20V±0.05 3) Standard Charge Current: 1250mA 4) Standard Charge Time: 3 hours 5) Standard Discharge Cut-off Voltage: 2.50V 6) Standard Discharge Current: 500mA 7) Standard Discharge Cut-off Current: 30mA 8) Max. Constant Discharge Current: 20A 9) Dimension: (D)18.40*(H)65.60mm 10) Cycle Life: Over 500 charge & discharge cycles 11) Weight: Max. 49.0g
	KP-IMR18650-2600	Li-Mn	3.7V 2600mAh		40A	1) Min. Capacity: 2500mAh 2) Charge Voltage: 4.20V±0.05 3) Standard Discharge Cut-off Voltage: 2.5V 4) Continuous Maximum Charge Current: 4.0A 5) Max. Constant Discharge Current: 40.0A 6) Max. Plus Discharge Current: 60A 7) Dimension: (D)18.40*(H)65.00mm 8) Cycle Life: Over 500 charge & discharge cycles 9) Weight: Max. 48.5g
	KP-IMR18650-2900	Li-ion	3.7V 2900mAh		10A	1) Min. Capacity: 2800mAh 2) Charge Voltage: 4.20V±0.05 3) Standard Charge Current: 1400mA 4) Standard Charge Time: 3 hours 5) Standard Discharge Cut-off Voltage: 2.50V 6) Standard Discharge Current: 580mA 7) Standard Discharge Cut-off Current: 30mA 8) Max. Constant Discharge Current: 10A 9) Dimension: (D)18.50*(H)66.00mm 10) Cycle Life: Over 500 charge & discharge cycles 11) Weight: Max. 48.0g
	KP-IMR18650-3200	Li-ion	3.7V 3200mAh		20A	1) Min. Capacity: 3100mAh 2) Charge Voltage: 4.20V±0.05 3) Standard Charge Current: 1000mA 4) Standard Charge Time: 5 hours 5) Standard Discharge Cut-off Voltage: 2.50V 6) Max. Constant Discharge Current: 20A 7) Standard Discharge Cut-off Current: 30mA 8) Dimension: (D)18.50*(H)66.00mm 9) Cycle Life: Over 500 charge & discharge cycles 10) Weight: Max. 49.0g
Button Top	KP-IMR18650-2000	Li-Mn	3.7V 2000mAh		22A	1) Min. Capacity: 1900mAh 2) Charge Voltage: 4.20V±0.05 3) Standard Charge Current: 1000mA 4) Standard Charge Time: 3 hours 5) Standard Discharge Cut-off Voltage: 2.75V 6) Standard Discharge Current: 400mA 7) Standard Discharge Cut-off Current: 30mA 8) Max. Constant Discharge Current: 22A 9) Dimension: (D)18.50*(H)66.50mm 10) Cycle Life: Over 500 charge & discharge cycles 11) Weight: Max. 46.0g
	KP-IMR18650-2100	Li-Mn	3.7V 2100mAh		30A	1) Min. Capacity: 2000mAh 2) Charge Voltage: 4.20V±0.05 3) Standard Charge Current: 1000mA 4) Standard Charge Time: 3 hours 5) Standard Discharge Cut-off Voltage: 2.75V 6) Standard Discharge Current: 420mA 7) Standard Discharge Cut-off Current: 30mA 8) Max. Constant Discharge Current: 30A 9) Dimension: (D)18.50*(H)66.50mm 10) Cycle Life: Over 500 charge & discharge cycles 11) Weight: Max. 48.0g
	KP-IMR18650-2250	Li-ion	3.7V 2250mAh		10A	1) Min. Capacity: 2150mAh 2) Charge Voltage: 4.20V±0.05 3) Standard Charge Current: 1100mA 4) Standard Charge Time: 3 hours 5) Standard Discharge Cut-off Voltage: 2.75V 6) Standard Discharge Current: 550mA 7) Standard Discharge Cut-off Current: 30mA 8) Max. Constant Discharge Current: 10A 9) Dimension: (D)18.50*(H)66.50mm 10) Cycle Life: Over 500 charge & discharge cycles 11) Weight: Max. 45.0g
	KP-IMR18650-2500	Li-Mn	3.7V 2500mAh		20A	1) Min. Capacity: 2400mAh 2) Charge Voltage: 4.20V±0.05 3) Standard Charge Current: 1250mA 4) Standard Charge Time: 3 hours 5) Standard Discharge Cut-off Voltage: 2.50V 6) Standard Discharge Current: 500mA 7) Standard Discharge Cut-off Current: 30mA 8) Max. Constant Discharge Current: 20A 9) Dimension: (D)18.50*(H)66.50mm 10) Cycle Life: Over 500 charge & discharge cycles 11) Weight: Max. 49.0g
	KP-IMR18650-2600	Li-Mn	3.7V 2600mAh		40A	1) Min. Capacity: 2500mAh 2) Charge Voltage: 4.20V±0.05 3) Standard Discharge Cut-off Voltage: 2.5V 4) Continuous Maximum Charge Current: 4.0A 5) Max. Constant Discharge Current: 40.0A 6) Max. Plus Discharge Current: 60A 7) Dimension: (D)18.50*(H)66.50mm 8) Cycle Life: Over 500 charge & discharge cycles 9) Weight: Max. 48.5g

Type	Model	Type	Nominal Voltage/Capacity	Photo	Max. Constant Discharge Current	Specifications
Button Top	KP-IMR18650-2900	Li-ion	3.7V 2900mAh		10A	1) Min. Capacity: 2800mAh 2) Charge Voltage: 4.20V±0.05 3) Standard Charge Current: 1400mA 4) Standard Charge Time: 3 hours 5) Standard Discharge Cut-off Voltage: 2.50V 6) Standard Discharge Current: 580mA 7) Standard Discharge Cut-off Current: 30mA 8) Max. Constant Discharge Current: 10A 9) Dimension: (D)18.50*(H)66.50mm 10) Cycle Life: Over 500 charge & discharge cycles 11) Weight: Max. 48.0g
	KP-IMR18650-3200	Li-ion	3.7V 3200mAh		20A	1) Min. Capacity: 3100mAh 2) Charge Voltage: 4.20V±0.05 3) Standard Charge Current: 1000mA 4) Standard Charge Time: 5 hours 5) Standard Discharge Cut-off Voltage: 2.50V 6) Max. Constant Discharge Current: 20A 7) Standard Discharge Cut-off Current: 30mA 8) Dimension: (D)18.50*(H)66.50mm 9) Cycle Life: Over 500 charge & discharge cycles 10) Weight: Max. 49.0g
	KP-IMR26650-3500	Li-Mn	3.7V 3500mAh		20A	1) Min. Capacity: 3400mAh 2) Charge Voltage: 4.20V±0.05 3) Standard Charge Current: 1700mA 4) Standard Charge Time: 3 hours 5) Standard Discharge Cut-off Voltage: 2.75V 6) Standard Discharge Current: 700mA 7) Standard Discharge Cut-off Current: 30mA 8) Max. Constant Discharge Current: 20A 9) Dimension: (D)26.50*(H)67.00mm 10) Cycle Life: Over 500 charge & discharge cycles 11) Weight: Max. 93.0g
	KP-IMR26650-4200	Li-Mn	3.7V 4200mAh		50A	1) Min. Capacity: 4100mAh 2) Charge Voltage: 4.20V±0.05 3) Standard Charge Current: 1700mA 4) Standard Charge Time: 3 hours 5) Standard Discharge Cut-off Voltage: 2.75V 6) Standard Discharge Current: 700mA 7) Standard Discharge Cut-off Current: 30mA 8) Ultra Discharge Current: 50A 9) Dimension: (D)26.50*(H)67.00mm 10) Cycle Life: Over 500 charge & discharge cycles 11) Weight: Max. 95.0g
	KP-IMR26650-5200	Li-Mn	3.7V 5200mAh		30A	1) Min. Capacity: 5100mAh 2) Charge Voltage: 4.20V±0.05 3) Standard Charge Current: 1700mA 4) Standard Charge Time: 3 hours 5) Standard Discharge Cut-off Voltage: 2.75V 6) Standard Discharge Current: 700mA 7) Standard Discharge Cut-off Current: 30mA 8) Ultra Discharge Current: 30A 9) Dimension: (D)26.50*(H)67.00mm 10) Cycle Life: Over 500 charge & discharge cycles 11) Weight: Max. 95.0g

Remarks:

Type	Description	View of Positive Pole	View of Negative Pole
Bare Cell	Excellent high drain lithium cell manufactured by top brands.		
Flat Top	Flat nickel-plated steel welded on the negative pole.		
Button Top	Button nickel-plated steel welded on the positive pole.		

* Please contact the email info@keeppower.com.cn for more information.